UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/810,715	03/29/2004	Yuusuke Sato	251072US3RD	9352
OBLON, SPIVAK, MCCLELLAND, MAIER & NEUSTADT, P.C. 1940 DUKE STREET			EXAMINER	
			LEWIS, BEN	
ALEXANDRIA, VA 22314		•	ART UNIT	PAPER NUMBER
		1745		
			NOTIFICATION DATE	DELIVERY MODE
			05/21/2007	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

patentdocket@oblon.com oblonpat@oblon.com jgardner@oblon.com

,	Application No. Applicant(s)					
	10/810,715	SATO ET AL.				
Office Action Summary	Examiner	Art Unit				
	Ben Lewis	1745				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication. - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).						
Status						
1) Responsive to communication(s) filed on 2a) This action is FINAL. 2b) This action is non-final. 3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims						
4) Claim(s) 1-23 is/are pending in the application. 4a) Of the above claim(s) 12-23 is/are withdrawn from consideration. 5) Claim(s) is/are allowed. 6) Claim(s) 1-11 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/or election requirement.						
Application Papers						
 9) ☐ The specification is objected to by the Examiner. 10) ☑ The drawing(s) filed on 29 March 2004 is/are: a) ☑ accepted or b) ☐ objected to by the Examiner. Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a). Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152. 						
Priority under 35 U.S.C. § 119						
 12) ⊠ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) ⊠ All b) ☐ Some * c) ☐ None of: 1. ☒ Certified copies of the priority documents have been received. 2. ☐ Certified copies of the priority documents have been received in Application No 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 						
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date See Continuation Sheet. 4) Interview Summary (PTO-413) Paper No(s)/Mail Date 5) Notice of Informal Patent Application 6) Other:						

Art Unit: 1745

DETAILED ACTION

Election/Restrictions

Applicant's election with traverse of Species I, claims 1-11, in Paper filed March 28th 2007 is acknowledged. The traversal is on the ground(s) that the outstanding office action does not identify search classifications and that a search and examination of the entire application would not place a serious burden on the examiner.

This is not found persuasive because species require a different field of search (e.g., searching different classes/subclasses or electronic resources, or employing different search queries); and/or the prior art applicable to one species would not likely be applicable to another species.

The requirement is still deemed proper and is therefore made FINAL. Therefore, claims 12-23 are withdrawn from consideration.

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Art Unit: 1745

2. Claims 1-3 and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Okamoto (U.S. Pub. No. 2002/0182460 A1) in view of Muller et al. (U.S. Patent No. 6,777,116 B1)

With respect to claim 1, Okamoto disclose a fuel cell power plant (title) wherein the fuel cell power plant is provided with a water tank 1 and a methanol tank 2 "fuel tank", a vaporizer 5 which vaporizes the water and methanol, a reformer 6 which generates reformate gas from the gaseous mixture of water vapor and methanol vapor, and a carbon monoxide oxidizer 7 which removes carbon monoxide (CO) from the reformate gas (Paragraph 0022). A reformer 6 generates hydrogen rich gas from vaporized methanol and a fuel cell stack 8 generates electric power by a reaction of hydrogen rich gas (See Abstract).

Okamoto does not specifically mention wherein the fuel includes dimethyl ether. However, Muller et al. disclose a direct dimethyl ether fuel cell (title) wherein in a direct dimethyl ether fuel cell, a fuel stream comprising dimethyl ether is supplied directly to the fuel cell anode for direct oxidation therein. Thus, a direct dimethyl ether fuel cell system comprises a system for supplying a dimethyl ether fuel stream to the anode. The fuel stream may contain other reactants and may desirably be supplied as a liquid. For instance, water is a reactant and the fuel stream may be an aqueous solution of dimethyl ether (Col 3 lines 38-55). Muller et al. also teach that particularly at low current densities, a direct dimethyl ether fuel cell may show efficiency advantages over other fuel cell types. For instance, an efficiency advantage may be obtained over direct methanol fuel cells (Col 4 lines 7-22). Therefore it would have been obvious to one of

ordinary skill in the art to incorporate the dimethyl ether of Muller et al. as a fuel in the fuel cell system of Okamoto because Muller et al. teach that particularly at low current densities, a direct dimethyl ether fuel cell may show efficiency advantages over other fuel cell types. For instance, an efficiency advantage may be obtained over direct methanol fuel cells (Col 4 lines 7-22).

Muller et al. teach that if methanol/DME/water fuel streams are employed, it might be desired to increase the DME concentration during low fuel cell loads in order to obtain higher efficiency (Col 5 lines 60-67). Okamoto does not specifically teach a single fuel tank storing a fuel comprising ether, water and an alcohol. However, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use a single tank for the fuel of Okamoto because making separate components integral is considered obvious. In re Larson, 340 F.2d 965, 968, 144 USPQ 347, 349 (CCPA 1965) (A claim to a fluid transporting vehicle was rejected as obvious over a prior art reference which differed from the prior art in claiming a brake drum integral with a clamping means, whereas the brake disc and clamp of the prior art comprise several parts rigidly secured together as a single unit. The court affirmed the rejection holding, among other reasons, "that the use of a one piece construction instead of the structure disclosed in [the prior art] would be merely a matter of obvious engineering choice.")

With respect to claims 2 and 3, Muller et al. teach that if methanol/DME/water fuel streams are employed, it might be desired to increase the DME concentration during low fuel cell loads in order to obtain higher efficiency (Col 5 lines 60-67).

With respect to claim 11, Okamoto teach that the Specifically, the reformer 6 generates hydrogen by oxidizing methanol in the presence of an oxidation catalyst (Paragraph 0025). Regarding shift catalyst, Okamoto teach that the carbon monoxide oxidizer 7 performs catalytic combustion due to the preferential oxidation of the carbon monoxide in the reformate gas to generate hydrogen-rich gas with a low level of carbon monoxide, using noble metal catalysts such as ruthenium (Ru) and platinum (Pt) (Paragraph 0026).

3. Claim 4 is rejected under 35 U.S.C. 103(a) as being unpatentable over Okamoto (U.S. Pub. No. 2002/0182460 A1) in view of Muller et al. (U.S. Patent No. 6,777,116 B1) and further in view of Zhang et al. (U.S. Pub. No. 2003/0110841 A1).

With respect to claim 4, Okamoto as modified by Muller et al. et al. disclose a fuel cell in paragraph 2 above. Okamoto as modified by Muller et al. et al. teach that methanol may be replaced by gasoline or any liquid material containing hydrocarbons (Paragraph 0022). Okamoto as modified by Muller et al. do not specifically mention

Art Unit: 1745

wherein the fuel includes ethanol. However, Zhang et al. disclose a direct dimethyl ether fuel cell wherein in typically, the fuel will be methanol and the fuel cell system will thus be a DMFC though other fuels may be used (Paragraph 0013). Zhang et al. also teach that the fuel typically used is methanol though other fuels such as, for example, ethanol or dimethyl ether could be used (Paragraph 0024). Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to use ethanol as a fuel in the fuel cell system of Okamoto as modified by Muller et al. because substituting art recognized equivalents known for the same purpose is obvious See MPEP 2144.06

4. Claim 5 is rejected under 35 U.S.C. 103(a) as being unpatentable over Okamoto (U.S. Pub. No. 2002/0182460 A1) in view of Muller et al. (U.S. Patent No. 6,777,116 B1) and further in view of Pan et al. et al. (U.S. Pub. No. 2004/0110046 A1).

With respect to claim 5, Okamoto as modified by Muller et al. disclose a fuel cell in paragraph 2 above. Okamoto does not specifically mention wherein the fuel includes less than 10wt% methanol. However, Pan et al. disclose a fuel delivery system (title) wherein the optimal range of the fuel concentration is determined based on the type of the fuel cell and the intended usage of the fuel cell. For example, the optimal fuel concentration for a direct methanol fuel cell may range from 3%-5% by weight in order to minimize fuel crossover. However, if the fuel cell is to be used in an application that requires high power output, the optimal range of fuel concentration may become 5%-

Application/Control Number: 10/810,715

Art Unit: 1745

10% by weight (Paragraph 0032). Therefor it would have been obvious to one of ordinary skill in the art to incorporate the methanol concentration of Pan et al. into the fuel cell system of Okamoto as modified by Muller et al. because Pan et al. teach that the optimal fuel concentration for a direct methanol fuel cell may range from 3%-5% by weight in order to minimize fuel crossover (Paragraph 0032).

5. Claim 6 is rejected under 35 U.S.C. 103(a) as being unpatentable over Okamoto (U.S. Pub. No. 2002/0182460 A1) in view of Muller et al. (U.S. Patent No. 6,777,116 B1) and further in view of Pan et al. et al. (U.S. Pub. No. 2004/0110046 A1).

With respect to claim 6, Okamoto as modified by Muller et al. disclose a fuel cell in paragraph 2 above. Okamoto as modified by Muller et al. do not specifically mention wherein the fuel includes less than 10wt% methanol. However, Pan et al. disclose a fuel delivery system (title) wherein the optimal range of the fuel concentration is determined based on the type of the fuel cell and the intended usage of the fuel cell. For example, the optimal fuel concentration for a direct methanol fuel cell may range from 3%-5% by weight in order to minimize fuel crossover. However, if the fuel cell is to be used in an application that requires high power output, the optimal range of fuel concentration may become 5%-10% by weight (Paragraph 0032). Therefore it would have been obvious to one of ordinary skill in the art to incorporate the methanol concentration of Pan et al. et al. into the fuel cell system of Okamoto as modified by Muller et al. because Pan et al. et al. teach that the optimal fuel concentration for a

Page 8

Art Unit: 1745

direct methanol fuel cell may range from 3%-5% by weight in order to minimize fuel crossover (Paragraph 0032).

With respect to wherein the fuel includes dimethyl ether water and methanol, the disclosure Okamoto et al. as modified by Muller et al. differs from Applicant's claims in that Okamoto et al. as modified by Muller et al. do not disclose wherein the mixing ratio of dimethyl ether and water is in a range of 1:3 and 1:4. However, Muller et al. recognize the need to increase the concentration of dimethyl ether in a dimethyl ether, methanol and water mixture. Muller et al. teach that If methanol/DME/water fuel streams are employed, it might be desired to increase the DME concentration during low fuel cell loads in order to obtain higher efficiency (Col 5 lines 60-67). Therefore, it would have been within the skill of the ordinary artisan to adjust the DME/ water ratio in the methanol/DME/ water mixture of Okamoto such that the DME/water ratio is within the applicants claimed DME/water ratio range in order to obtain higher efficiency during low fuel cell loads. *Discovery of optimum value of result effective variable in known process is ordinarily within skill of art.* In re Boesch, CCPA 1980, 617 F.2d 272, 205 USPQ215.

6. Claim 7 and 8 are rejected under 35 U.S.C. 103(a) as being unpatentable over Okamoto (U.S. Pub. No. 2002/0182460 A1) in view of Muller et al. (U.S. Patent No. 6,777,116 B1) and further in view of Yonestu et al. (U.S. Patent No. 6,506,513 B1).

With respect to claim 7, Okamoto as modified by Muller et al. disclose a fuel cell in paragraph 2 above. Okamoto as modified by Muller et al. do not specifically mention

Application/Control Number: 10/810,715

Art Unit: 1745

Page 9

wherein the tank comprises a cartridge unit, a valve unit, a holding unit and a supplying unit. However, Yonestu et al. disclose a liquid fuel-housing tank for fuel cell (title) Yonsetu et al. teaches a fuel tank 1 "cartridge", a valve 23, a connecting section 33 "holding member" and a pathway 3 "supply unit" (Col 10 lines 40-67) (See Figs 10A, 11A and 12). Yonsetu et al. also teach that it is required that the fuel be taken out from the tank stably so as to obtain a stable output, and that the fuel cell has the high performance of the initial rising characteristics. Since the rising characteristics depends on the initial flow rate of the fuel from the fuel tank into the fuel cell body, it is necessary to supply the fuel promptly to the fuel cell body. In other words, it is required that the fuel tank has a mechanism for promptly supplying the fuel in the initial period (Col 2 lines 10-25). Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate the fuel tank of Yonsetu et al. into the fuel cell system of Okamoto as modified by Muller et al. because Yonsetu et al. teach that it is required that the fuel be taken out from the tank stably so as to obtain a stable output, and that the fuel cell has the high performance of the initial rising characteristics. Since the rising characteristics depends on the initial flow rate of the fuel from the fuel tank into the fuel cell body, it is necessary to supply the fuel promptly to the fuel cell body (Col 2 lines 10-25).

7. With respect to claim 8, Muller et al. teach that if methanol/DME/water fuel streams are employed, it might be desired to increase the DME concentration during low fuel cell loads in order to obtain higher efficiency (Col 5 lines 60-67).

Application/Control Number: 10/810,715

Art Unit: 1745

8. Claim 9 is rejected under 35 U.S.C. 103(a) as being unpatentable over Okamoto (U.S. Pub. No. 2002/0182460 A1) in view of Muller et al. (U.S. Patent No. 6,777,116 B1) and further in view of Suzuki et al. (U.S. Pub. No. 2002/0068206A1).

With respect to claim 9, Okamoto as modified by Muller et al. disclose a fuel cell system in paragraph 2 above. Okamoto as modified by Muller et al. do not specifically mention a vacuum heat insulation container containing the combustor, containing the vaporizer, the reformer and the CO gas removal apparatus. However, Suzuki et al. discloses a fuel cell power system wherein the first hydrogen storage vessel 11, the catalytic combustor 17 and the first three way valve 15 are housed within a thermal insulation housing 25 having a vacuum insulation structure. The thermal insulation housing 25 prevents the combustion heat generated by the catalytic combustor 17 from diffusing outside the system and maintains the temperature of the first hydrogen storage vessel 11 at about 250 °C to about 280 °C (Paragraph 0019). Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate the vacuum heat insulation housing of Suzuki et al. to contain the combustor, vaporizer, reformer and CO gas removal apparatus of Okamoto as modifid by Muller et al. because Suzuki et al. teach that the thermal insulating housing maintains the temperature of the system components within the housing (Paragraph 0019).

9. Claim 10 is rejected under 35 U.S.C. 103(a) as being unpatentable over Okamoto (U.S. Pub. No. 2002/0182460 A1) in view of Muller et al. (U.S. Patent No. 6,777,116 B1) and further in view Kaneko et al. (U.S. Pub. No. 2001/0021469 A1).

With respect to claim 10, Okamoto as modified by Muller et al. disclose a fuel cell system in paragraph 2 above. Okamoto teach that Specifically, the reformer 6 generates hydrogen by oxidizing methanol in the presence of an oxidation catalyst (Paragraph 0025).

Okamoto as modified by Muller et al. do not specifically mention a reforming catalyst of an alumina and at least one material selected from the group consisting of Rh, Pd, Pt and Cu. However, Kaneko et al. disclose a methanol reforming catalyst wherein, the methanol reforming catalyst may contain other component except the catalytic compound. For example, in order to enlarge a reaction surface area, large specific surface area base material such as alumina, silica, or the like, that is impregnated with the above catalytic compound, may be used (Paragraph 0038). Kaneko et al. also teach that Pd component is alloyed with Zn, generation of CO due to the above methanol decomposition reaction expressed by following Eq. (f2) can be suppressed while holding the high temperature stability (Paragraph 0032). Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate the alumina and palladium of Kaneko et al. as reforming catalyst in the reformer of Okamoto as modified by Muller et al. because Kaneko et al. teach that in order to enlarge a reaction surface area, large specific surface area base material such

Application/Control Number: 10/810,715 Page 12

Art Unit: 1745

as alumina, silica, or the like, that is impregnated with the above catalytic compound, may be used (Paragraph 0038) and methanol decomposition can be suppressed using Pd/Zn catalyst (Paragraph 0032).

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Ben Lewis whose telephone number is 571-272-6481. The examiner can normally be reached on 8:30am - 5:30pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Patrick Ryan can be reached on 571-272-1292. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

SUSYTSANG-FOSTER
PRIMARY EXAMINER

Application No. 10/810,715

Continuation of Attachment(s) 3). Information Disclosure Statement(s) (PTO/SB/08), Paper No(s)/Mail Date :8/10/04, 2/16/05, 9/19/05, 9/30/05, 12/16/05, 6/4/06, 6/15/06, 7/11/06, 12/11/06, 4/9/07.